

TEMPOCAMO WARNINGS AND INSTRUCTIONS

KEEP OUT OF REACH OF CHILDREN - DO NOT ALLOW UNAPPLIED LIQUID TO FREEZE

GENERAL INFORMATION

TempoCamo coatings are designed to provide nonporous surfaces with temporary color and protection. TempoCamo dries to a tough flexible vinyl film which can be easily removed by peeling manually or using a scrub brush with warm water. TempoCamo is formulated to protect against environmental hazards, salt corrosion, bugs, tar, metal shavings and physical protection from minor nicks, scratches and abrasion.

APPLICATION

Always test all surfaces to be coated with TempoCamo by applying a small amount to an area and allowing to dry thoroughly. TempoCamo may be applied by brush, spray or roller. Must be applied between 65°F and 160°F. After curing, TempoCamo will become brittle and harder to remove at freezing temperatures and may melt at temperatures over 160°F. Keep out of moving parts.

BEST APPLICATION

Prepare surface to be coated. Always test a small spot to test how it will be affected. Some discoloration may occur. Open carefully.

Stir thoroughly to mix color and achieve consistent viscosity. Colors can be mixed in small amounts to achieve desired tints or colors.

Apply like paint by using a brush.

Allow TempoCamo to dry before handling. Drying times will vary depending on humidity and temperature. TempoCamo may be dry to the touch for recoating in less than one hour at 85°F. For best results allow to cure overnight before handling. TempoCamo can be force-dried with warm air.

After curing, TempoCamo will provide a temporary, durable coating. But it has its limitations. Experiment and test the coating on your item to determine how much wear it can handle. Remember that is designed to peel off after use. Ambient temperatures can affect removal. At lower temperatures, cured TempoCamo will become brittle and chip off when removed. Allow cured TempoCamo to warm to room temperature to peel off in larger pieces. At higher temperatures, TempoCamo will melt. Do not apply to items that will exceed 160°F.

When uncured in liquid state, it acts like paint. Spills, drips and mistakes may smear and be messy. Most times it will be easier to remove if you let it dry/cure. Then, you can peel or scrape it off. You can usually scrape it off with your thumbnail or a toothpick. Do not use a hard or sharp objects that may damage what's beneath the coating.

Keep away from moving parts. When uncured and/or wet, TempoCamo may seep or run into seams or openings between moving parts. Do not allow TempoCamo to affect the operation of tools or equipment by allowing TempoCamo into places that glue, paint, or liquid should not be allowed to enter. Uncured TempoCamo may conduct electricity.

Emergency telephone number:

Velocityehs (24 hours per day):

1-813-248-0585 (INTL)

1-800-255-3924 (United States)

**READ PRECAUTIONS
BEFORE USING!
STIR WELL BEFORE USE**



**READ PRECAUTIONS
BEFORE USING!**

**Stir Before Using
DO NOT LET LIQUID FREEZE**

PRODUCT DESCRIPTION: Tempocamo Protective coatings are designed to provide nonporous surfaces with temporary protection against environmental hazards, salt corrosion, bugs, tar, metal shavings and physical protection from minor nicks, scratches and abrasions. When applied, Tempocamo protective coating dries to a tough flexible vinyl film which can be easily removed by using high pressure water or by peeling manually. Applications would include the protection of painted surfaces on cars, trucks, tractors, bumpers, heavy equipment, metal frame windows, boats, cultured marble, polyester/glass shower stalls, and plumbing fixtures **USES:** Tempocamo may be used as a masking material to protect surfaces from paint overspray and as a spray booth coating.

APPLICATION: Always test all surfaces to be coated with Tempocamo by applying a small amount to an area and allowing to dry thoroughly. On older surfaces that show oxidation, prepare surface with liquid auto wax before application of Tempocamo coating. Tempocamo may be applied by spray or roller application as received with no thinning required. Spray equipment can be either conventional air, airless, or HVLP system. Tempocamo must be protected from freezing and must be applied at temperatures no lower than 65°F or higher than 160°F. Tempocamo must be stirred with moderate agitations for several minutes before using. Tempocamo may be dried with forced hot air or infrared heat.

WARRANTY DISCLAIMER: The statements made on this label, product bulletins, brochures, or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide for approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Proprietary Specialty Coatings Co. does not make nor does it authorize and agent or representative to make EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING ANY WARRANTY MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY CONCERNING THIS MATERIAL. This material conforms to Proprietary's quality control standards. Any liability whatsoever of Proprietary Specialty Coatings Co. to the buyer or user of this product is limited to the purchaser's cost of the product itself.

Potential Health Hazards: Eyes: Irritating to eyes. If material is splashed into eyes, flush with large amounts of water until irritation subsides. **Skin:** Frequent or prolonged contact may cause skin irritation. If skin contact occurs, flush area with large amounts of water. Use soap if available. **Inhalation:** Use in well ventilated areas. **Personal Protection:** Application where contact is likely, or for prolonged or repeated contact wear safety glasses with side shields, long sleeves, and impervious gloves. **Storage:** Store material in ambient temperature. Keep containers closed when not in use. Do not allow material to enter waterways or sewers. Dispose of in accordance with all local, state and federal laws.

HMIS	1
FLAMMABILITY	0
REACTIVITY	-

KEEP OUT OF THE REACH OF CHILDREN!

Warranty: The statements made on this label, product bulletins, or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide for approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Proprietary's Specialty Coatings does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material, except that it conforms to Proprietary's quality control standards. Any liability whatsoever of Proprietary Specialty Coatings Company to the buyer or user of this product is limited to the purchaser's cost of the product itself.

WARNING! SEE PRECAUTIONS!
Lockwood Eagle 1, LLC

NET CONTENTS – 5 GALLONS
1001 Eagle Ridge

PROTECT FROM FREEZING!
Billings, MT 59101